


PIN DESCRIPTION:

Pin NO.	Signal
1	VSS
2	VDD
3	V0
4	RS
5	R/W
6	E
7	D0
8	D1
9	D2
10	D3
11	D4
12	D5
12	D6
12	D7

NOTES:

1. DISPLAY TYPE : STN, YELLOW-GREEN, TRANSPARENT/POSITIVE.
2. DRIVE METHOD: 1/16 DUTY, 1/5BIAS, VDD: 2.4~5.5V, VOP=4.5V
3. VIEWING DIRECTION: 6 O'CLOCK.
4. CONTROLLER DRIVER: S6B0032X01-B0CY
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. BACKLIGHT: LED.
8. CONNECTOR: HEAT SEAL
9. MATERIAL TO BE ROHS COMPLIANT.
10. UNMARKED TOLERANCE: ±0.3mm.



VERSION	MODIFYCONTENT	MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
		CUSTOMER APVL	DATE		
		DRAWN	SCALE	TITLE	
		DFTG CHK	UNIT	mm	
		ENGR CHK	MODEL	M11602F-G-2	
		APPROVAL			
				DWG NO	PAGE
					1/1