


1. Display Data Address:

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Line 1	80	81	82	83	84	85	86	87	88	89	8A	8B	8C	8D	8E	8F
Line 2	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	CA	CB	CC	CD	CE	CF

2. Pin Connections:

Pin No	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Signal	V _{SS}	V _{DD}	V _{SS}	V _{DD}	V _O	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	



NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN MODE, TRANFLECTIVE/POSITIVE.
2. DRIVE METHOD: 1/16DUTY, 1/5BIAS, VDD=5.0 V, VOP=4.2 V,
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER: KS0066U AND KS0065B OR EQUIVALENT.
5. OPERATING TEMP: -20 °C ~ 70 °C.
6. STORAGE TEMP: -30 °C ~ 80 °C.
7. BACKLIGHT TYPE: LED BACKLIGHT YELLOW-GREEN BOTTOM MODE.
8. ALL UNMARKED TOLERANCES: ±0.5.
9. MEASURE UP RoHS

Unmarked Tolerance: ±0.5mm

Display Data Address

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Line 1	80	81	82	83	84	85	86	87	88	89	8A	8B	8C	8D	8E	8F
Line 2	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	CA	CB	CC	CD	CE	CF

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN MODE, TRANFLECTIVE/POSITIVE.
2. DRIVE: KS0066U and KS0065B OR EQUIVALENT
3. VIEWING ANGLE: 6 O'CLOCK.
4. PIN CONNECTION:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	VLED	VLSS