



CONNECTION PIN:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED(+)	LED(-)

DISPLAY DATA ADDRESS:

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Line 1	80	81	82	83	84	85	86	87	88	89	8A	8B	8C	8D	8E	8F
Line 2	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	CA	CB	CC	CD	CE	CF
Line 3	90	91	92	93	94	95	96	97	98	99	9A	9B	9C	9D	9E	9F
Line 4	D0	D1	D2	D3	D4	D5	D6	D7	D8	D9	DA	DB	DC	DD	DE	DF

NOTES:

1. DISPLAY TYPE: STN, GRAY MODE, TRANSFLECTIVE/POSITIVE .
2. DRIVE METHOD: DUTY=1/16,BIAS=1/4 ,VDD=5.0V,VOP=4.2V
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER:ST7066U-0A AND ST7065C OR EQUIVALENT.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
- 7 LED BACKLIGHT: YELLOW-GREEN.
- 8 ALL UNMARKED TOLERANCES: ±0.5mm.
- 9 符合ROHS标准

CUSTOMER APVL		DATE	
DRAWN	SCALE	TITLE MODULE	
DFTG CHK	UNIT mm		
ENGR CHK	APPROVAL	MODEL MI1604E	
MULTI-INNO TECHNOLOGY CO.,LTD		DWG NO 00	PAGE 1/11

VERSION	MODIFYCONTENT
---------	---------------