


DETAIL A:



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
V _{SS}	V _{CC}	V _{EE}	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTE:

1. DISPLAY TYPE: STN/YELLOW-GREEN MODE
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
4. DRIVE METHOD: 1/16 DUTY 1/5 BIAS
5. LCD OPERATING VOLTAGE: 4.7V
6. OPERATING TEMP: -20°C--+70°C
7. STORAGE TEMP: -30°C--+80°C
8. CONTROLLER: S6A0069X05-C0CX(KS0066UP-05CC)
9. BACKLIGHT TYPE: LED
10. BEZEL IS TO BE PAINTED BLACK
11. ALL UNMARKED TOLERANCES: ±0.3mm

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI2402F	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME:	UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	