


PIN DESCRIPTION

PIN	
1	NC
2	LED+
3	LED-
4	GND
5	VDD
6	VDD
7	OTPD
8	OTPG
9	RESET
10	RS
11	WR
12	RD
13	DB0
14	DB1
15	DB2
16	DB3
17	DB4
18	DB5
19	DB6
20	DB7
21	DB8
22	DB9
23	DB10
24	DB11
25	DB12
26	DB13
27	DB14
28	DB15
29	MPU
30	CS
31	GND
32	NC

DETAIL A(ITO):



- NOTES:
1. DISPLAY TYPE: CSTN(65K COLOR)
  2. VIEWING DIRECTION: 6:00
  3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
  4. LCD CONTROLLER: S6B33B6
  5. DRIVE METHOD: 1/128 DUTY 1/5 BIAS
  6. VDD: 3.0V
  7. OPERATING VOLTAGE: 10.6V
  8. BACKLIGHT: 1CHIP-WHITE LED
  9. OPERATING TEMP.: -20°C~70°C
  10. STORAGE TEMP.: -30°C~80°C
  11. UNMARKED TOLERANCE: ±0.3
  12.   MEANS IMPORTANT DIMENSION

**MULTI-INNO TECHNOLOGY CO.,LTD**

DRAWN BY:	TITLE: M1128128NK	
CHECKED BY:	DWG NO: G-1	SCALE:
APPROVED BY:	DWG NAME: M1128128NK G-1	UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	

SYMBOL	CONTENT	DATE