


PIN CONNECTION:

NO.	SYMBOL
1	N/C
2	V0
3	V4
4	V3
5	V2
6	V1
7	C2-
8	C2+
9	C1+
10	C1-
11	C3+
12	Vour
13	Vss
14	VDD
15	SID
16	SCLK
17	RS
18	RESETB
19	CS1B
20	N/C



DETAIL A
DISPLAY PATTERN

NOTES:

1. DISPLAY TYPE: FSTN MODE, TRANSFLECTIVE/POSITIVE.
2. DRIVEMETHOD: DUTY=1/65, BIAS=1/9, VDD=3.0V, VOP=9.5V.
3. VIEWING DIRECTION: 6 O'CLOCK.
4. DRIVER: S6B0724A01-BOCY.
5. OPERATING TEMP: -20°C~70°C.
6. STORAGE TEMP: -30°C~80°C.
7. BACKLIGHT TYPE: EDGE BACKLIGHT, Y-G, LEDA-LEDK=4.2V.
8. UNMARKED TOLERANCE: ±0.3mm.
9. RoHS COMPLIANT.

CUSTOMER APVL		DATE	
DRAWN		SCALE	TITLE
DFTG CHK		UNIT	MODULE
ENGR CHK		mm	
APPROVAL			MODEL
			GS-GG1065601FFYJ/R
GENDA TECHNOLOGY LTD		DWG NO	PAGE
		00	1/4

VERSION	MODIFYCONTENT
---------	---------------