



NO.	PIN	NO.	PIN	NO.	PIN
1	CS1	11	D5	21	CAP2-
2	RES	12	D6	22	V1
3	A0	13	D7	23	V2
4	WR	14	VDD	24	V3
5	RD	15	VSS	25	V4
6	D0	16	VOUT	26	V0
7	D1	17	CAP3+	27	C86
8	D2	18	CAP1-	28	P/S
9	D3	19	CAP1+		
10	D4	20	CAP2+		

- NOTES:
 1. DISPLAY TYPE: FSTN
 2. VIEWING DIRECTION: 6:00
 3. POLARIZER MODE: REFLECTIVE/POSITIVE
 4. DRIVE METHOD: 1/49 DUTY 1/8 BIAS
 5. LCD OPERATING VOLTAGE: 9.0V
 6. OPERATING TEMP.: 0°C-+50°C
 7. STORAGE TEMP.: -20°C-+60°C
 8. CONTROLLER: NT7532H-BDT
 9. CONNECTOR: FPC
 10. WITHOUT BACKLIGHT
 11. UNMARKED TOLERANCES: ±0.3mm
 12. THE CONTROL DIMENSION MASK TO BE:
 13. REQUIREMENTS ON ENVIROMENTAL PROTECTION ROHS

MUTLI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI12048A-G	
CHECKED BY:	DWG NO: G-4	
APPROVED BY:	DWG NAME:	UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	