



PIN	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	NC
6	VG
7	NC
8	NC
9	XVO
10	VO
11	NC
12	NC
13	VSS
14	VDD
15	SDA
16	SCLK
17	AO
18	RSTB
19	CSB
20	NC

- DISPLAY TYPE: FSTN
- VIEWING DIRECTION: 6:00
- POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- OPERATING TEMP: -20° --- +70° C
- STORAGE TEMP: -30° --- +80° C
- LCD OPERATING VOLTAGE: Δ 8.7V VDD=3.0V
- DRIVE METHOD: 1/65 DUTY 1/9BIAS
- CONTROLLER: ST7567
- BACKLIGHT: LED (White; 4 DIES) V=4V (TYPE) I=60mA
- CONNECTOR: FPC
- UNMARKED TOLERANCES: ±0.3mm
- THE CONTROLLED DIMENSION MASK TO BE
- REQUIREMENT ON ENVIRONMENTAL PROTECTION: RoHS



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI12864J-G-8	
CHECKED BY:	DWG NO: G-2	
APPROVED BY:	DWG NAME: G-2	SCALE: UNIT: mm
CONFIRMED BY:	G-2	SHEET NO: 1 OF 1

	SYM	VER	DESCRIPTION	DATE
Δ	G-2		CHANGE LCD OPERATION VOLTAGE VALUE	2008. 4. 1