



PIN	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	NC
6	VG
7	NC
8	NC
9	XV0
10	V0
11	NC
12	NC
13	VSS
14	VDD
15	SDA
16	SCLK
17	A0
18	RSTB
19	CSB
20	NC

- 1. DISPLAY TYPE: STN BLUE
- 2. VIEWING DIRECTION: 6:00
- 3. POLARIZER MODE: TRANSMISSIVE/ NEGATIVE
- 4. OPERATING TEMP: -20° --- +70° C
- 5. STORAGE TEMP: -30° --- +80° C
- 6. LCD OPERATING VOLTAGE: Δ 8.7V VDD=3.0V
- 7. DRIVE METHOD: 1/65 DUTY 1/9BIAS
- 8. CONTROLLER: ST7567
- 9. BACKLIGHT: LED(White; 4 DIES) V=4V (TYPE) I=60mA
- 10. CONNECTOR: FPC
- 11. UNMARKED TOLERANCES: \pm 0.3mm
- 12. THE CONTROLLED DIMENSION MASK TO BE
- 13. REQUIREMENT ON ENVIRONMENTAL PROTECTION: RoHS



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI12864J-G-8A	
CHECKED BY:	DWG NO: G-2	
APPROVED BY:	DWG NAME: G-2	SCALE: mm
CONFIRMED BY:	G-2	SHEET NO: 1 OF 1

SYMBOL	VERSION	DESCRIPTION	DATE
Δ	G-2	CHANGE LCD OPERATION VOLTAGE VALUE	2008. 4. 1

MISSI
NEGA