



PIN	SYMBOL	PIN	SYMBOL
1	NC	16	VSS
2	CS1	17	VOUT
3	RES	18	CAP3-
4	A0	19	CAP1+
5	VR	20	CAP1-
6	RD	21	CAP2-
7	D0	22	CAP2+
8	D1	23	V1
9	D2	24	V2
10	D3	25	V3
11	D4	26	V4
12	D5	27	V5
13	D6	28	VR
14	D7	29	C86
15	VDD	30	IRS

DETAIL A:



DETAIL B:



NOTES:

- | | |
|-------------------------------|-----------------------|
| 1. DISPLAY TYPE: | STN/BLUE MODE |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSMISSIVE/NEGATIVE |
| 4. DRIVE METHOD: | 1/65 DUTY 1/7 BIAS |
| 5. LCD OPERATING VOLTAGE: | 8.9V |
| 6. VDD: | 5.0V |
| 7. OPERATING TEMP.: | -20°C~+70°C |
| 8. STORAGE TEMP.: | -30°C~+80°C |
| 9. CONTROLLER: | S1D15605D11B |
| 10. WITH LED BACKLIGHT(WHITE) | |
| 11. CONNECTOR: | FPC |
| 12. UNMARKED TOLERANCE: | ±0.3mm |
| 13. RφHS | |

MULTI-INNO TECHNOLOGY CO., LTD

DRAWN BY:	TITLE: MI12864P-G-2	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: MI12864P-G-2G-1	UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	