


1	2	3	4	5	6	7	8	9	10	11	12
FG	VSS	VDD	VOUT	VEE	WR	RD	CE	C/D	HALT	RESET	DO
13	14	15	16	17	18	19	20	21	22	23	24
D1	D2	D3	D4	D5	D6	D7	NC	AL	KR	AR	KL

DETAIL A:



NOTES:

1. DISPLAY TYPE: STN/BLUE MODE
2. VIEWING DIRECTION: 12:00
3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
4. DRIVE METHOD: 1/128 DUTY 1/12 BIAS
5. LCD OPERATING VOLTAGE: 15.0V
6. OPERATING TEMP: 0°C-+50°C
7. STORAGE TEMP: -20°C-+60°C
8. CONTROLLER: T6963C
9. BACKLIGHT: LED(DC 7.0V 115-130mA,WHITE,EIGHT LAMPS EACH SIDE)
10. BEZEL IS TO BE PAINTED BLACK
11. ALL UNMARKED TOLERANCES: ±0.3mm

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI160128A-1	
CHECKED BY:	DWG NO: G-4	
APPROVED BY:	SCALE:	
CONFIRMED BY:	UNIT: mm	
	DWG NAME: MI160128A-1 G-4	SHEET NO: 1 OF 1