


NOTES:

1. DISPLAY TYPE: FSTN, TRANSLUCENT/POSITIVE.
2. DRIVE METHOD: 1/160DUTY, 1/13BIAS, VDD=3.3 V, VOP=19.2 V.
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER: NT7701F3 OR EQUIVALENT.
5. OPERATING TEMP: -20 °C ~ 70 °C.
6. STORAGE TEMP: -30 °C ~ 80 °C.
7. BACKLIGHT TYPE: 5 WHITE LED BACKLIGHT EDGE MODE. Vf= 18.0V
8. UNMARKED TOLERANCES: ±0.2.
9. RoHS COMPLIANT.

PIN CONNECTION:

PIN	1	2	3	4	5	6	7	8	9
DESC	GND	FLM	CL1	CL2	M	VDD	LED	VEE	D3
PIN	10	11	12	13	14	15	16	17	18
DESC	D2	D1	D0	NC	NC	NC	NC	GND	GND



DISPLAY PATTERN

CUSTOMER APVL		CUSTOMER		DATE	
DRAWN		SCALE		TITLE	
DFTG CHK		UNIT		TITLENO	
ENGR CHK		mm		MODEL	
APPROVAL				MI160160J-T	
MULTI-INNO TECHNOLOGY CO.,LTD.				DWG NO	PAGE
				DWGNO	PAGE