


Pin1 Connections:

Pin NO.	Signal
1	FG
2	VSS
3	VDD
4	VO
5	/WR
6	/RD
7	/CE
8	C/D
9	/RST
10	DB0
11	DB1
12	DB2
13	DB3
14	DB4
15	DB5
16	DB6
17	DB7
18	FS
19	Vout
20	VLED+
21	VLED-

NOTES:

1. DISPLAY TYPE :STN,BLUE MODE, TRANSMISSIVE/NEGATIVE.
2. DRIVE METHOD:1/128 DUTY,1/12BIAS,VDD=5V,VOP=18.5V.
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER:T6963C OR EQUIVALENT
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: WHITE,EDGE,VA-VK=5V
8. UNMARKED TOLERANCE: ±0.5mm.

DISPLAY PATTERN



CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	DATE	SCALE	TITLE
DFTG CHK		UNIT	
ENGR CHK		mm	
APPROVAL			MODEL
			MI240128A-3
VERSION	MODIFYCONTENT	MULTI-INNO TECHNOLOGY CO.,LTD.	DWG NO
			MI13
			PAGE
			1/1