



FPC DESCRIPTION

| PIN | SYMBOL |
|-----|--------|
| 1 | LED_K |
| 2 | LED_A |
| 3 | VSS |
| 4 | VB0+ |
| 5 | VB1+ |
| 6 | VB1- |
| 7 | VB0- |
| 8 | VA0+ |
| 9 | VA1+ |
| 10 | VA1- |
| 11 | VA0- |
| 12 | VLCD |
| 13 | VDD |
| 14 | VSS |
| 15 | VR1 |
| 16 | VR0 |
| 17 | CD |
| 18 | CS0 |
| 19 | RST |
| 20 | D0 |
| 21 | D1 |
| 22 | D2 |
| 23 | D3 |
| 24 | D4 |
| 25 | D5 |
| 26 | D6 |
| 27 | D7 |
| 28 | VSS |
| 29 | NC |
| 30 | NC |

Note:

1. Operating Temp: -20°C/+60°C
2. Storage Temp: -40°C/+70°C
3. IC DRIVER: UC1611S
4. DUTY=1/128, BIAS=1/12, VLCD=16V, VDD=3.3V
5. Rohs Compliant
6. LCD MODE: STN, Blue, Transmissive, negative
7. Flat connector 30 pins
8. Fixing by plastic snap-in