



I/O PORTS

NO.	SYMBOL
1	VLCD
2	V2
3	V3
4	V4
5	V5
6	VSS
7	GND
8	VDD
9	FRM
10	CP
11	DF
12	LOAD
13	D.OFF
14	GND
15	D3
16	D2
17	D1
18	D0

- NOTES:
- | | |
|---------------------------|---------------------------------------|
| 1. DISPLAY TYPE: | FSTN |
| 2. VIEWING DIRECTION: | 9:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. DRIVE METHOD: | 1/240 DUTY 1/12 BIAS |
| 5. LCD OPERATING VOLTAGE: | 15.2V VDD=3.0V |
| 6. OPERATING TEMP.: | -10°C~+60°C |
| 7. STORAGE TEMP.: | -20°C~+70°C |
| 8. CONNECTOR: | FPC |
| 9. DRIVER: | S6B0794X01-BOCZ(2)+S6B0796X01-BOCZ(1) |
| 10. BACKLIGHT TYPE: | NONE |
| 11. UNMARKED TOLERANCES: | ±0.3mm |

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	TITLE: MI320240N-G-1	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME:	UNIT: mm
CONFIRMED BY:	SHEET NO: OF	