



| Pin Assignment | |
|----------------|------------|
| NO. | SYMBOL |
| 1 | NC |
| 2 | VSS |
| 3 | NC |
| 4 | NC |
| 5 | NC |
| 6 | NC |
| 7 | NC |
| 8 | NC |
| 9 | NC |
| 10 | NC |
| 11 | VDD |
| 12 | BS1 |
| 13 | BS2 |
| 14 | NC |
| 15 | CS# |
| 16 | RES# |
| 17 | D/C# |
| 18 | R/W# (WR#) |
| 19 | E/RD# |
| 20 | DO |
| 21 | D1 |
| 22 | D2 |
| 23 | D3 |
| 24 | D4 |
| 25 | D5 |
| 26 | D6 |
| 27 | D7 |
| 28 | IREF |
| 29 | VCOMH |
| 30 | VCC |
| 31 | NC |

Specification

1. Display: OLED (White)
2. Format: 128*64
3. Driver IC: SSD1305Z
4. General Tolerance: ± 0.3
5. Operate temp: $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Storage temp: $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
6. DUTY: 1/64
7. RoHS Compliant