


No:	PIN NAME
1	LED_A
2	LED_K1
3	LED_K2
4	NC
5	/RESET
6	DB15
7	DB14
8	DB13
9	DB12
10	DB11
11	DB10
12	DB9
13	DB8
14	DB7
15	DB6
16	DB5
17	DB4
18	DB3
19	DB2
20	DB1
21	DB0
22	/RD
23	/WR
24	RS
25	CS
26	VDDIO
27	VDD
28	IM0
29	GND

- NOTES:
- 1.DISPLAY TYPE: TFT-LCD
 - 2.VIEWING DIRECTION: 6:00
 - 3.MAIN LCD DRIVE IC: ILJ163
 - 4.POLARIZER MODE: TRANSMISSIVE/POSITIVE
 - 5.DRIVE METHOD: 1/160 DUTY
 - 6.VDD: 2.8V(TYP); VDDIO: 1.8V(TYP)
 - 7.BACKLIGHT: WHITE LED-2CHIP/IF I=40mA, V=3.2V(TYP)
 - 8.OPERATING TEMP: -20°C ~ 70°C
 - 9.STORAGE TEMP: -30°C ~ 80°C
 - 10.UNMARKED TOLBRANCE: ±0.30
 - 11.IMPORTANT DIMBNSION:
 12. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS



MULTI-INNO TECHNOLOGY CO.,LTD.

			DRAWN BY:	TITLE: MI0177FT-2	 SCALE:
			CHECKED BY:	DWG NO:	
G-1	NEW ISSUE	08.11.18	APPROVED BY:	DWG NAME:	SHEET NO: 1 OF 1
REV	DESCRIPTION	DATE	CONFIRMED BY:		