



弯折后效果图



B/L circuit  
I=45mA  
U=2.9-3.5V



- NOTES:
1. DISPLAY TYPE: TFT
  2. VIEWING DIRECTION: 6:00
  3. POLARIZER MODE: TRANSMISSIVE/POSITIVE
  4. LCD CONTROLLER: HX8340-B
  5. DRIVE METHOD: 1/220 DUTY
  6. VDD: 3.0V IOVCC:1.8/2.8V
  7. BACKLIGHT: 3CHIP-WHITE LED(parallel)
  8. OPERATING TEMP: -20°C~70°C
  9. STORAGE TEMP: -30°C~80°C
  10. UNMARKED TOLERANCE:±0.2
  11. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS

No.	PIN NAME
1	GND
2	VDD
3	/CS
4	RS
5	WR/SCL
6	RD
7	DO
8	D1
9	D2
10	D3
11	D4
12	D5
13	D6
14	D7
15	D8
16	D9
17	D10
18	D11
19	D12
20	D13
21	D14
22	D15
23	/LCD_RESET
24	SDI
25	IM0
26	LED3-
27	LED2-
28	LED1-
29	LED+
30	IM2
31	X-
32	X+
33	Y-
34	Y+

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY: MI0220ST-1			
ME CHECKED BY:		DWG NO:	
EE CHECKED BY:		UNIT: mm	
SYMBOL	CONTENT	DATE	APPROVED BY:
		SCALE: 1:1	SHEET NO: 1 OF 1