




P1	LED-A	P21	DB11
P2	LED K	P22	DB10
P3	GND	P23	DB9
P4	VCI	P24	DB8
P5	IM0	P25	DB7
P6	IM1	P26	DB6
P7	IM2	P27	DB5
P8	IM3	P28	DB4
P9	FRAME	P29	DB3
P10	RESET	P30	DB2
P11	VSYSN	P31	DB1
P12	HSYSN	P32	DB0
P13	DOTCLK	P33	RD
P14	ENABLE	P34	WR
P15	DB17	P35	DC/SCK
P16	DB16	P36	SDD
P17	DB15	P37	SDI
P18	DB14	P38	VDD3
P19	DB13	P39	CS
P20	DB12	P40	GND



T/P CON

1	X+
2	Y-
3	X-
4	Y+



- NOTES:
1. OPERATING TEMPERATURE: -10°C TO 60°C
 2. STORAGE TEMPERATURE: -20°C TO 70°C
 3. DRIVE IC: S6D04H0
 4. DISPLAY MODE: TRANSFLECTIVE(TF-C+),Normal White
 5. CORRESPONDING CONNECTOR:XF2M-4015-1A
 6. ROHS COMPLIANCY (环保标准)
 7. GENERAL TOLERANCE: ±0.20mm