



The hole for nominal size 3mm se lf-tapping screw attachment depth 3.5mm(4 p oint)  
Suggested applying torque 0.15-0.2Nm

- Notes:
- 1.unmarked tolerance:±0.50mm;
  - 2.Display Type: a-Si TFT ;
  - 3.Operating Temperature:-30°C~+85°C;
  - 4.Storage Temperature:-30°C~+85°C;
  - 5.Gray Scale Inversion: 12 o'clock;
  - 6.CN2 LED Power source Connector:SHLP-06V-S-B(JST) or Compatible, Mating Connector:SM06B-SHLS-TF(JST) or Compatible;
  - 7.CN1 Connector type: 089H33-000100-G2-R (STARCONN)
  - 8.Requirement on Environment Protection: Q/S0002.

Pin No.	Symbol
1	GND
2	CK
3	Hsync
4	Vsync
5	GND
6	R0
7	R1
8	R2
9	R3
10	R4
11	R5
12	GND
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	GND
20	B0
21	B1
22	B2
23	B3
24	B4
25	B5
26	GND
27	ENAB
28	VCC
29	VCC
30	R/L
31	U/D
32	NC
33	GND

PIN	Symbol	Cable color
1	AN1	Red
2	AN2	Red
3	AN3	Red
4	CA1	White
5	CA2	Blue
6	CA3	Black

CONTROL DIMENTION:			MULTI-INNO TECHNOLOGY CO.,LTD.			
REFERENCE DIMENTION:	( )					
APPROVED:	Maxiaoping	2009.11.27	MODEL NAME	MI0570B1T	3rd ANGLE	
CHECKED:	Suyuefeng	2009.11.27	PART NAME	LCM	UNIT	mm
DESIGNED:	Linxiang	2009.11.27	DRAWING NUMBER	YGT 1-00	SCALE	25
			MATERIAL NUMBER	MI0570B1T	PAGE	1/1