


**Note:**

1. Brightness : 500 cd/m<sup>2</sup> (Typ)
2. 40 PIN Connector: JAE FA5B040HP1 or Equivalent.
3. 10 PIN Connector: Molex: 54548-1071 or Equivalent.
4. Tolerance is ±0.3 unless otherwise noted.
5. Sunlight readable type
6. For RoHS.



40 PIN FUNCTIONS									
1	U/D	11	VSS	21	G5	31	R3		
2	NC	12	ADJ	22	G4	32	VSS		
3	HSYNC	13	B5	23	G3	33	R2		
4	VLED	14	B4	24	VSS	34	R1		
5	VLED	15	B3	25	G2	35	RO		
6	VLED	16	VSS	26	G1	36	VSS		
7	VCC	17	B2	27	G0	37	VSS		
8	VSYNC	18	B1	28	VSS	38	DCLK		
9	DE	19	B0	29	R5	39	VSS		
10	VSS	20	VSS	30	R4	40	L/R		

				DATE:	05/21/08'	MUTLTI-INNO TECHNOLOGY CO.,LTD.			
				DRAWN:					
				CHECK:		DWG. NO.	MI0570KT		
AUTH	DESCRIPTION	DATE	APPROVED	APPROVE:		UNITS	M M	REV.	A
REVISIONS						SCALE	1 / 1 SHEET 1 OF 1		

