




no.	CTPIC
1	VCC
2	RST
3	SCL
4	ATTB
5	SDA
6	GND
7	NC
8	NC
9	NC
10	NC

- NOTE:
1. Tolerance is ± 0.3 unless otherwise noted.
 2. LCM FPC matching connector: Molex 0541325062 or equivalent.
 3. For RoHS.
 4. Center brightness: 220 cd/m^2 (Typ), 175 cd/m^2 (Min.)
 5. Uniformity: 70% (Min.)
 6. * is important dimension.
 7. CTP matching connector : Molex 0545481071 or equivalent
 8. CTP IC: Pixcir M48.



LCM PIN FUNCTION

1 VLED+	11 HSD	21 G6	31 R4	41 VDDG/VGH
2 VLED-	12 B7	22 G5	32 R3	42 VEEG/VGL
3 VLED+	13 B6	23 G4	33 R2	43 AVDD
4 VLED-	14 B5	24 G3	34 R1	44 RSTB
5 GND	15 B4	25 G2	35 R0	45 NC
6 VCOM	16 B3	26 G1	36 GND	46 VCOM
7 DVDD	17 B2	27 G0	37 DCLK	47 DITH
8 MODE	18 B1	28 R7	38 GND	48 GND
9 DE	19 B0	29 R6	39 SHLR	49 NC
10 VSD	20 G7	30 R5	40 UPDN	50 NC